

product data

NEOX D

Description: A very viscous, brown oil.

Use: Designed primarily for sterntube lubrication, particularly where a non-circulatory oilfeed system is used and a labyrinth or face type seal is fitted.

Recommended for the lubrication of the trunnion bearings of Brown Bros. Retractable fin stabilisers.

Characteristics:	Viscosity @ 40°C	Approx. 370 cSt
	Viscosity @ 60°C	Approx. 80 cSt
	Density @ 15.5°C	Approx. 0.920 kg / ltr
	Pour point (IPT 15 / 65)	Approx. + 29°C
	Shelf life	Expected indefinite in sealed containers

- Performance Data:**
1. Provides a very high standard of lubrication and corrosion protection suitable for sterntube bearings.
 2. Absorbs any sea-water entering the sterntube to form a viscous, brown emulsion which remain stable and maintains excellent lubrication and corrosion protection properties.
 3. The oil and emulsion have very good adherence to metal surfaces, resisting wash off by water.
 4. Minimises oil leakage past a damaged or worn aft seal.
 5. Not recommended for use with rubber lip type seal systems.

Notes: This product should only be used for the applications specified. The supplier cannot accept responsibility if it is used in any other applications.

H.S.T.N.: 271019
REF: DM03/06A

the quality touch



FM 1851



EMS 40717

ACCREDITED TO THE ISO 9001 QUALITY
STANDARD AND THE ISO 14001
ENVIRONMENTAL MANAGEMENT STANDARD

Registered Office

Benjⁿ R. Vickers & Sons Ltd

Airedale Mills, 6 Clarence Road, Leeds LS10 1ND, England

Phone: +44 (0) 113 386 7654 Fax: +44 (0) 113 386 7676

Email: techserv@vickers-oil.com Website: www.vickers-oil.com

